

Cordone Specs

Tolerance applied (compared to usually applied) and sales format.

CORD CS (thickness)		ISO 3601-1 ORINGONE		ISO 3302-1 CLASS E1		ISO 3302-1 CLASS E2		FORMAT (length)	
mm	inch	mm	inch	mm	inch	mm	inch	m	ft
2,62	0,103	±0,08	±.003	±0,25	±.010	±0,40	±.016	60	196,9
3,00	0,118	±0,09	±.003	±0,25	±.010	±0,40	±.016	60	196,9
3,53	0,139	±0,10	±.004	±0,25	±.010	±0,40	±.016	60	196,9
4,00	0,157	±0,10	±.004	±0,25	±.010	±0,40	±.016	60	196,9
4,50	0,177	±0,10	±.004	±0,35	±.014	±0,50	±.019	60	196,9
5,00	0,197	±0,13	±.005	±0,35	±.014	±0,50	±.019	60	196,9
5,33	0,210	±0,13	±.005	±0,35	±.014	±0,50	±.019	60	196,9
5,50	0,217	±0,15	±.006	±0,35	±.014	±0,50	±.019	60	196,9
5,70	0,224	±0,15	±.006	±0,35	±.014	±0,50	±.019	60	196,9
6,00	0,234	±0,15	±.006	±0,35	±.014	±0,50	±.019	60	196,9
6,35	0,250	±0,15	±.006	±0,35	±.014	±0,50	±.019	60	196,9
6,50	0,256	±0,15	±.006	±0,40	±.016	±0,70	±.027	60	196,9
7,00	0,276	±0,15	±.006	±0,40	±.016	±0,70	±.027	50	164,1
7,50	0,295	±0,15	±.007	±0,40	±.016	±0,70	±.027	50	164,1
8,00	0,315	±0,18	±.007	±0,40	±.016	±0,70	±.027	50	164,1
8,40	0,331	±0,18	±.008	±0,40	±.016	±0,70	±.027	50	164,1
9,00	0,354	±0,20	±.008	±0,40	±.016	±0,70	±.027	20	65,6
9,50	0,374	±0,20	±.008	±0,40	±.016	±0,70	±.027	20	65,6
10,00	0,394	±0,20	±.008	±0,40	±.016	±0,70	±.027	20	65,6
10,82	0,426	±0,20	±.008	±0,50	±.019	±0,80	±.031	15	49,2
11,00	0,433	±0,20	±.008	±0,50	±.019	±0,80	±.031	15	49,2
12,00	0,472	±0,22	±.009	±0,50	±.019	±0,80	±.031	15	49,2
12,70	0,500	±0,23	±.009	±0,50	±.019	±0,80	±.031	15	49,2
13,00	0,512	±0,23	±.010	±0,50	±.019	±0,80	±.031	15	49,2
14,00	0,551	±0,25	±.011	±0,50	±.019	±0,80	±.031	10	32,8
14,40	0,567	±0,26	±.011	±0,50	±.019	±0,80	±.031	10	32,8
15,00	0,591	±0,27	±.011	±0,50	±.019	±0,80	±.031	10	32,8
16,00	0,630	±0,29	±.011	±0,50	±.019	±0,80	±.031	10	32,8
17,00	0,669	±0,30	±.012	±0,70	±.027	±1,00	±.039	10	32,8
18,00	0,709	±0,32	±.013	±0,70	±.027	±1,00	±.039	10	32,8
19,00	0,748	±0,34	±.013	±0,70	±.027	±1,00	±.039	10	32,8
20,00	0,787	±0,36	±.014	±0,70	±.027	±1,00	±.039	10	32,8
22,00	0,866	±0,39	±.015	±0,70	±.027	±1,00	±.039	8	26,2
24,00	0,945	±0,43	±.017	±0,70	±.027	±1,00	±.039	8	26,2
25,00	0,984	±0,45	±.017	±0,70	±.027	±1,00	±.039	8	26,2
26,00	1,024	±0,47	±.017	0,80	±.031	±1,30	±.051	6	19,7
28,00	1,102	±0,50	±.019	0,80	±.031	±1,30	±.051	6	19,7
30,00	1,181	±0,54	±.021	0,80	±.031	±1,30	±.051	6	19,7
40,00	1,575	±0,72	±.028	0,80	±.031	±1,30	±.051	6	19,7